

LED tape 60LED/m 12V



Voltage:	12 V DC
Qty LED:	60 LED/m
Can be cut into section:	5 cm
Typical power:	4,8 9,6 14 W/m
Max. luminous efficiency:	137 lm/W

Basic info

- PL LINE PRODUCT- PROFESSIONAL LINE, HIGHEST QUALITY, LUMINOSITY AND DURABILITY
- PROFESSIONAL PCB MOUNTING, ONLY BRAND-NAME LED DIODES (OSRAM,CITIZEN,CREE ETC.)
- FLEXIBLE LED TAPES, GOMAR PLUS PRODUCTION
- EASY INSTALLATION, CAN BE MOUNTED ON UNEVEN SURFACES
- UP TO 5 YEARS WARRANTY

LED tape is available typically in power version: 4,8 | 9,6 | 14 W/m, and colour temperature: 3000K, 4000K, 5000K, CRI80.

With our own production line we can customize LED tapes including parameters as:

- power per meter (W/m)
- colour temperature: 2200K, 2400K, 2700K, 3500K, 5700K, 6500K
- LEDs colour: red, green, blue, amber etc.
- Colour Rendering Index (Ra): CRI90, CRI97

Customized products are priced individually. Please check exemplary variants of power and brightness in chart below



Technical parameters

Voltage	12 V DC
Qty LED	60 LED/m
Can be cut into section	5 cm
Width	10 mm
Height	2 mm
Beam angle	120 °
Color rendering index (Ra)	80 Ra
Operating temperature	-25 °C - 60 °C
Storage temperature	-40 °C - 80 °C
IP degree	IP20
Typical power	4,8 9,6 14 W/m
Max. luminous efficiency	137 lm/W

Technical drawing

