

LED tape 008-050-08-03 SL 4,8 W/m 300 lm/m



Voltage:	12 V
Power:	4.8 W/m
Luminosity:	60 - 390 lm/m
Qty LED:	60 LED/m
Distance between LED:	16.6 mm
Can be cut into section:	5 cm

Basic info

- SL LINE PRODUCT (PRODUCT LINES: BL-BUDGET, EL-ECONOMIC, SL-STANDARD, PL-PROFESSIONAL)
- SL LINE - PROFITABLE ATTITUDE OF QUALITY/DURABILITY/LUMINOSITY TO PRICE
- MODULES CAN BE SPLIT INTO 5 CM SECTIONS (3LED)
- MODULES CAN BE JOINED INTO LONGER STRINGS (MAXIMUM LENGHT OF LED SECTIONS WITH ONE POWER-SUPPLY POINT: 5M)

Technical parameters

Variant	Cool white W
Voltage	12 V
Power	4.8 W/m
Luminocity	60 - 390 lm/m
Qty LED	60 LED/m
Distance between LED	16.6 mm
Can be cut into section	5 cm
Power of single LED	0.08 W
A/m	0.4 A/m
Width	8 mm
Height	2.5 mm
Color temperature / Wavelength scope	3000 - 6000 K
Wavelength scope	475 - 635 nm
Beam angle	120 °
Color rendering index (Ra)	80 Ra
Minimum operating temperature	-25 °C
Maximum Operating temperature	60 °C
Minimum storage temperature	-40 °C
Maximum storage temperature	80 °C
IP degree	20 IP

Technical drawing

