

LED tape 013-050-10-06 SL 14,4W/m W-WW



Voltage:	24 V
Power:	14.4 W/m
Luminosity:	550 - 1160 lm/m
Qty LED:	120 LED/m
Distance between LED:	8.3 mm
Can be cut into section:	5 cm

Basic info

- ADJUSTABLE COLOR TEMPERATURE: 3000-6000K
- CONTROLLED WITH 3 WIRES; JOINT ANODE (+) AND TWO WIRES (-) ONE FOR WARM COLOR, THE SECOND FOR COOL WHITE COLOR
- MODULE CAN BE SPLIT INTO 5 CM SECTIONS (6LED)
- MODULES CAN BE JOINED INTO LONGER STRINGS (MAXIMUM LENGHT OF LED SECTIONS WITH ONE POWER-SUPPLY POINT: 5M)

Technical parameters

Variant	Cool white W	Neutral white NW	Warm white WW
Voltage	24 V	24 V	24 V
Power	14.4 W/m	14.4 W/m	14.4 W/m
Luminosity	550 - 1160 lm/m	550 - 1160 lm/m	550 - 1160 lm/m
Qty LED	120 LED/m	120 LED/m	120 LED/m
Distance between LED	8.3 mm	8.3 mm	8.3 mm
Can be cut into section	5 cm	5 cm	5 cm
Power of single LED	0.12 W	0.12 W	0.12 W
A/m	0.64 A/m	0.64 A/m	0.64 A/m
Width	10 mm	10 mm	10 mm
Height	2.5 mm	2.5 mm	2.5 mm
Color temperature / Wavelength scope	3000 - 5000 K	3000 - 5000 K	3000 - 5000 K
Beam angle	120 °	120 °	120 °
Color rendering index (Ra)	80 Ra	80 Ra	80 Ra
Minimum operating temperature	-30 °C	-30 °C	-30 °C
Maximum Operating temperature	40 °C	40 °C	40 °C
Minimum storage temperature	-40 °C	-40 °C	-40 °C
Maximum storage temperature	80 °C	80 °C	80 °C
IP degree	20 IP	20 IP	20 IP