

LED tape 024-050-10-03 EL 14,4 W/m RGB



Voltage:	12 V
Power:	14.4 W/m
Luminosity:	45 - 190 lm/m
Qty LED:	60 LED/m
Distance between LED:	16.6 mm
Can be cut into section:	5 cm

Basic info

- MODULES CAN BE SPLIT INTO 5 CM SECTIONS (3LED)
- MODULES CAN BE JOINED INTO LONGER STRINGS (MAXIMUM LENGHT OF LED SECTION WITH ONE POWER-SUPPLY POINT: 5M)

Technical parameters

Variant	Red R	Green G	Blue B
Voltage	12 V	12 V	12 V
Power	14.4 W/m	14.4 W/m	14.4 W/m
Luminosity	45 - 190 lm/m	45 - 190 lm/m	45 - 190 lm/m
Qty LED	60 LED/m	60 LED/m	60 LED/m
Distance between LED	16.6 mm	16.6 mm	16.6 mm
Can be cut into section	5 cm	5 cm	5 cm
Power of single LED	0.24 W	0.24 W	0.24 W
A/m	1.2 A/m	1.2 A/m	1.2 A/m
Width	10 mm	10 mm	10 mm
Height	2.5 mm	2.5 mm	2.5 mm
Wavelength scope	475 - 635 nm	475 - 635 nm	475 - 635 nm
Beam angle	120 °	120 °	120 °
Minimum operating temperature	-25 °C	-25 °C	-25 °C
Maximum Operating temperature	60 °C	60 °C	60 °C
Minimum storage temperature	-40 °C	-40 °C	-40 °C
Maximum storage temperature	80 °C	80 °C	80 °C
IP degree	20 IP	20 IP	20 IP

Technical drawing

