

LED light bar 051-063-13-07 PL 57,6W/m 6900lm/m



Voltage:	24 V
Power:	57.6 W/m
Brightness:	6900 lm/m
Qty LED:	112 LED/m
Distance between LED:	9 mm
Can be cut into section:	6.3 cm

Basic info

- PL LINE PRODUCT- PROFESSIONAL LINE, HIGHEST QUALITY, LUMINOSITY AND DURABILITY
- PROFESSIONAL PCB MOUNTING, ONLY NAME-BRAND LED DIODES (OSRAM, CITIZEN, CREE ETC.)
- MODULES CAN BE SPLIT INTO 6.3CM SECTIONS (7LED)
- MODULES CAN BE JOINED INTO LONGER STRINGS (MAXIMUM LENGHT OF LED SECTION WITH ONE POWER-SUPPLY POINT: 1M), NEEDS COOLING

With our own production line we can customize LED light sources including parameters as:

- power (W/m)
- colour temperature: 2200K, 2400K, 2700K, 3500K, 5700K, 6500K
- LEDs colour (red, green, blue, amber etc.)
- Colour Rendering Index (Ra)

Customized products are priced individually

Technical parameters

Variant	Cool white W 5000K	Neutral white NW 4000K	Warm white WW 3000K
Voltage	24 V		
Power	57.6 W/m		
Brightness	6900 lm/m	6900 lm/m	6720 lm/m
Qty LED	112 LED/m		
Distance between LED	9 mm		
Can be cut into section	6.3 cm		
Power of single LED	0.51 W		
A/m	2.4 A/m		
Width	10 mm		
Height	2.5 mm		
Beam angle	120 °		
Color rendering index (Ra)	80 Ra		
Minimum operating temperature	-25 °C		
Maximum Operating temperature	60 °C		
Minimum storage temperature	-40 °C		
Maximum storage temperature	80 °C		
IP degree	20 IP		

Technical drawing

